

Multi Putty



Description

Two component multifunctional fine-grained polyester putty for filling unevenness especially on aluminum and galvanized surfaces.

Application

Multifunctional finishing putty for eliminating car and commercial vehicle body imperfections.

Characteristics

- It is characterized by easily work in thick and thin layers
- It can also be used as finishing putty
- After drying it produces a smooth, pin-hole free surface
- Does not clog the sandpaper
- Intended for manual/machine dry sanding.

Substrates

Steel, galvanized surfaces, aluminum, fiberglass plastics, polyester materials, OEM substrates*.

VOC: < 250 g/L
EU limit value: 2004/42/IB(b)(250)

Articles	Description	Pcs. / pack
2-210-2000	2 kg, w/hardener	6

Substrate pretreatment



Substrates to be treated must be cleaned, dried, degreased with C.A.R.FIT Silicone Remover and sanded

Application*



Add 2–3% BPO Hardener by weight



Pot life: 3–5 min at 20°C

Further treatment



16–30 min depending on ambient temperature



With P80–180



With P80–320 (intermediate sanding step of 100 grit should be observed)

Technical data

Color yellow
Density 1830 g/L

Storage



Keep away from direct sunlight

*Do not apply on one component (etch and anticorrosive) primers and thermoplastics. Application on paintworks is **not recommended**.